TESTBURY A CONTRACTOR	
HOSE CO. 2	

WESTBURY FIRE DEPARTMENT

Hose Compay #2





NFPA 1001 (2013) - 5.3.1

Name/Badge:

Co: Evaluation Type:

Instructor/Badge:

Instructors Signature: _____ Date:

	NO	YES
Has the FF verified regulator is disconnected from user FF's Facepiece		
Has the FF asked user FF to position themselves (knee or bend over) for easy change		
Has the FF fully closed the cylinder valve		
Has the FF ask user FF to bleed air from high and low pressure hoses		
Has the FF disconnected the high pressure hose from the cylinder		
Has the FF removed the empty cylinder from the harness assembly		
Has the FF verified the replacement cylinder has 90-100 % the rated capasity		
Has the FF placed new cylinder into the harness/backpack assembly		
Has the FF check the cylinder valve for damage and inspected O rig in hose fitting		
Has the FF connected the high pressure hose to the cylinder and hand tightened		
Has the FF slowly opened cylinder valve and listened for audible alarms		
(PASS and Vibe-alert) as well as listened for adudible air leaks		
Has the FF asked the using FF to donned regulator and taken a normal breath		
Has the FF's verified pressure readings at remote guage and heads up and verifing		
there is consistancy as per department standards		
Has the FF verbizilized removing SCBA from service, Writing work order and notifiying		
company officer when any faults are found in the SCBA		
Has Firefighter Displayed Compentacy on a two person SCBA Bottle Change		

Instructor Notes